

Godrej



TAKE NO CHANCES

**Fire Resisting
Filing Cabinets
(FRFC)**



Underwriters' Laboratory, USA.



*Fire Resistant for 120 minutes.
Are your office documents worth it?*

More protection through robust construction

The body of a Godrej Fire Resisting Filing Cabinet is fabricated using modern precision tooling and sheet metal working equipment. Only prime quality CRCA steel is used. The thickness of the steel addresses both the structural strength requirements as well as the need to minimise absorption thereby conduction of heat. The cabinet has separate inner and outer shells reinforced in vital places to form a rigid integral body.

Formidable resistance to heat

The unique Godrej fire resisting compound has a cellular structure. Cast in situ between the outer and inner shells of the body, including the inner and outer walls of each drawer unit, it provides a highly efficient shield against heat. It can withstand temperature exceeding 1000°C (1800°F) and providing as much resistance to flames and hot gases as a 610 mm (24") thick concrete wall.

A special Tongue-and-groove construction employed to prevent the passage of flames and hot gases to the interior of the drawer.

Each drawer of the Fire Resisting Cabinet has an independent five-sided enclosure heavily insulated with the unique Godrej fire resisting compound. This makes each drawer a separate fully insulated compartment which will protect its contents even if one or more of the other drawers are inadvertently left open.

Independently tested for performance

- Listed at Underwriters' Laboratory Inc. USA (except 1 drawer FRFC) for 1hr & 2hr ratings for Fire Endurance, Fire and Impact as well as Explosion hazards as per UL : 72 Class 350.

The 2-hour fire-impact test involved heating the cabinet in a specially designed furnace to over 1000°C (1800°F), dropping it from a height of 9 metres (30') and subsequently heating it again in an inverted position to 1010°C (1800°F). Even after the entire duration of the test, the paper records inside the drawers were found to be usable, demonstrating its superior fire and impact resisting capabilities.

Effortless movement of drawers

The drawers of the Godrej Fire Resisting Filing Cabinet move on specially designed double extension telescopic slides each having eight heavy duty steel bearings.

Safe and ingenious locking

- Emergency latch is provided with a self-closing latch which enables users to shut the drawers almost instantaneously during emergencies.
- A sturdy automatic locking mechanism that is centrally controlled by one Godrej high-precision 6-lever dual control lock, which serves all the drawers. This lock is fitted on the topmost drawer allowing individual drawers to be kept open for use while the rest are locked.
- A 3-wheel numerical combination lock on the top drawer in lieu of/in addition to the high-precision 6-lever dual control lock. This lock offers a choice of nearly 10,00,000 combinations for setting and resetting.
- Individual locks on all drawers can also be provided (optional) at an extra cost.

Specifications of 1 hr Rated FRFC (UL 72, Class 350 Fire & Impact)							
Overall Cabinet dimensions							
	Height		Width		Depth		Weight Kg
	mm	inch	mm	inch	mm	inch	
4-Drawers	1600	63	552	22	805	31	470
3-Drawers	1218	48	552	22	805	31	370
2-Drawers	836	32	552	22	805	31	240
1-Drawer	454	17	552	22	805	31	110
Drawer Dimensions							
4-Drawers	280	11	388	15	635	25	
Specifications of 1 hr Rated 670-D Series FRFC (UL 72, Class 350 Fire & Impact)							
Overall Cabinet dimensions							
	Height		Width		Depth		Weight Kg
	mm	inch	mm	inch	mm	inch	
4-Drawers	1600	63	552	22	670	26	370
3-Drawers	1218	48	552	22	670	26	285
2-Drawers	836	32	552	22	670	26	185
1-Drawer	454	17	552	22	670	26	100
Drawer Dimensions							
4-Drawers	280	11	388	15	499	25	

Specifications of 2 hr Rated FRFC (UL 72, Class 350 Fire & Impact)							
Overall Cabinet dimensions							
	Height		Width		Depth		Weight Kg
	mm	inch	mm	inch	mm	inch	
4-Drawers	1608	63	560	22	835	33	510
3-Drawers	1226	48	560	22	835	33	415
2-Drawers	844	32	560	22	835	33	260
1-Drawer	462	17	560	22	835	33	135
Drawer Dimensions							
4-Drawers	280	11	388	15	635	25	
Specifications of 2 hr Rated 700-D Series FRFC (UL 72, Class 350 Fire & Impact)							
Overall Cabinet dimensions							
	Height		Width		Depth		Weight Kg
	mm	inch	mm	inch	mm	inch	
4-Drawers	1608	63	560	22	700	27	425
3-Drawers	1226	48	560	22	700	27	305
2-Drawers	844	32	560	22	700	27	200
1-Drawer	462	17	560	22	700	27	120
Drawer Dimensions							
4-Drawers	280	11	388	15	499	25	

All weights and sizes are approximate. Tolerances - Weight: ±3%. Dimensions: ±1%.



TAKE NO CHANCES

Godrej & Boyce Mfg. Co. Ltd. Security Equipment Division.

Regd. Off.: Plant 17, Pirojshanagar, Vikhroli, Mumbai 400079. INDIA.
Tel.: (91-22) 67964753-63. Fax: (91-22) 67961509.
Email: secure@godrej.com Website: www.godrej.com

GODREJ OVERSEAS OFFICES

Godrej & Boyce, P.O. Box 8549, A2-004, SAIF Zone, **Sharjah**, UAE. Tel.: 971 6 5570866.
Fax: 971 6 5570966. Email: godrejdb@emirates.net.ae, ratan@godrej.ae, homiyar@godrej.ae

Godrej & Boyce Mfg. Co. Ltd., Post Box No. 21030-00505, Mamlaka Road, House No. A3,
Ground Floor, Next to Stella Awinja Hostel, **Nairobi**, Kenya.
Tel.: 00 254 20 2044123. Mobile: 00 254 733647187. Email: fredrickcorrea@godrejafrika.com

Godrej & Boyce Mfg. Co. Ltd.
Dabab Street, Opposite Riyadh Chamber of Commerce, PO Box: 221890,
Riyadh: 11311, Kingdom of Saudi Arabia. Cell: 00 966 501 365788
Tel.: 00 966 1 4025345 / 4024068. Fax: 00 966 1 4025369
Email: godrejdb@emirates.net.ae, taj@godrejsaudi.com, ranga@godrejsaudi.com

In view of the Godrej policy of continuous development and improvement, the dimensions and specifications may be changed without prior notice or obligation.
Colours of the products shown in this catalogue may not match the actual colour of the product due to printing limitations.